ORDER NO. MKE0012753C1

Service Manual

HARD DISK RECORDER

S> SHOWSTOPPER™

PV-HS1000 / PV-HS2000 / PV-HS3000



SPECIFICATIONS

Q D	EC	IEIC	`лт	DNG

ITEM	SP	ECIFICATION	1	2	3	ITEM	SPECIFI	ICATION	1	2	3
General	Operating voltage: Power Consumption:	120 V AC@60 Hz 19 W (Power OFF) 27 W (Power ON) 28 W (Power ON)	0	C	000	Dimensions/ Weight	Height: 80 mm Width: 432 m Depth: 289 m Weight (net): 5.8 kg	nm nm	0	0	, c
Tuner	MTS		0	С	0	Audio/Video	Audio output level:	2.0 V [P-P]		_	Į
Innut	Tuner: Composite:	Type F Phono x 2		_		Signals	Video output level: Video output impedance:	1.0 V [P-P] 75 Ω	ľ	0	10
Input Connectors	Audio: S-Video:	Phono (L+R) x 2 4-pin miniature DIN		C		Operating/ Storage Conditions	Operating temp. range: +5 °C Storage temp. range: -20 °C		0	0	, (
Output	Composite: Audio: S-Video:	Phono x 2 Phono (L+R) x 2 4-pin miniature DIN	0	С			HDD Capacity:	20.4 GB 30.0 GB	0	0	
Connectors	Telephone: Serial Control: IR Blaster	RJ-11, 2 wire DB-9				Record	Video compression format: Audio compression format: Recording level:		0	-000	C
							Recording time:	20 h/ 10 h/ 6.5 h 30 h/ 15 h/ 10 h 61 h/ 30.5 h/ 20.5 h	0	-	-
						MODEM	Speed: 56 kbps	01 1// 30.3 1// 20.3 11	0	0	Ŧ

^{1.} PV-HS1000

Weight and dimensions shown are approximate. Design and specifications are subject to change without notice.

Note: Please ignore the Service Manual Order No. MKE0003750C1.

© 2000 Matsushita-Kotobuki Electronics Industries LTD. All rights reserved. Unauthorized copying and distribution is a violation of law.

⚠ WARNING

This service information is designed for experienced repair technicians only and is not designed for use by the general public. It does not contain warnings or cautions to advise non-technical individuals of potential dangers in attempting to service a product. Products powered by electricity should be serviced or repaired only by experienced professional technicians. Any attempt to service or repair the product or products dealt with in this service information by anyone else could result in serious injury or death.

^{2.} PV-HS2000

^{3.} PV-HS2000

Panasonic®

IMPORTANT SAFETY NOTICE

There are special components used in this equipment which are important for safety. These parts are marked by \triangle in the Schematic Diagrams, Circuit Board Diagrams, Exploded Views and Replacement Parts List. It is essential that these critical parts should be replaced with manufacturer's specified parts to prevent shock, fire or other hazards. Do not modify the original design without permission of manufacturer.

1. REPLACEMENT PARTS LIST

BEFORE REPLACING PARTS, READ THE FOLLOWING:

1.1. REPLACEMENT NOTES

1.1.1. General Notes

Use only original replacement parts:
 To maintain original function and reliability of repaired units, use only original replacement parts which are listed with their part numbers in the parts list.

2. IMPORTANT SAFETY NOTICE

Components identified by the sign \triangle have special characteristics important for safety. When replacing any of these components, use only the specified parts.

- 3. Parts with no Ref. No. in "EXPLODED VIEW" are not supplied. And some Ref. No. will be skipped. Be sure to make your orders of replacement parts according to the parts list.
- 4. Parts different in shape or size may be used. However, only interchangeable parts will be supplied as service replacement parts.

1.2. REPLACEMENT PARTS LIST

Ref.	Part Name	Part No.				
No.		PV-HS1000	PV-HS2000	PV-HS3000		
26 OPEF	OPERATING INSTRUCTION	9600021	9600007	96000068		
		LSQT0197A	LSQT0269A	LSQT0302A		
		(PASC)	(PASC)	(PASC)		
27	REMOTE CONTROL	2000018	2000018	2000018		
		2000015	2000015	2000015		
		2000010	2000010			
<u> 29</u>	END CAP, PAKG, HINGE CUT	8000019	8000019	8000019		
<u>30</u>	ACCESSORY KIT	3800000	3800000	3800000		
<u>31</u>	BOX, BRN, UNIV, ACC KIT	8000010	8000010	8000010		
<u>32</u>	SHIPPING, BOX	8000007	8000012	8000024		
<u>34</u>	CONN, MODULAR DPX, T ADPTR, RJ- 11	1700034	1700034	1700034		
<u>35</u>	ADPTR, SERIAL, EXT, 9P F DSUB (RTV) - 15P M (DIRECTV)	1700038	1700038	1700038		
<u>36</u>	ADPTR, DSS, EXT, 9P F DSUB (RTV) - RJH (DSS)	1700039	1700039	1700039		
37	IR EMTR, DL MONO PLUG, 7", BL	2000014	2000014	2000014		
38	CBL, A/V, 3 CONN, 6", BLK	2100010	2100010	2100010		
<u>39</u>	CBL, S-VIDEO, 6", BLK	2100011	2100011	2100011		
<u>40</u>	CBL, DB-9, SERIAL, M-F, 6", BEIGE, SHIELDED	2100015	2100015	2100015		
41	CBL, AC PWR, NI SPT2, 6"	2100037	2100037	2100037		
<u>42</u>	CABLE, TELEPHONY, RJ-11, 26AWG, 25", GREY	2100029	2100029	2100029		
<u>43</u>	BATTERIES, ALKALINE, AA, 1.5V, (2 PK), PANASONIC	2300002	2300002	2300002		
44	QUICK SETUP GUIDE	9600008	9600008	9600008		
		LSQC016(PASC)	LSQC016(PASC)	LSQC016(PASC		

2. EXPLODED VIEW

